

VERO VX



Next level performance in a versatile format


by **FUNKTION-ONE**

INTRODUCTION



Vero VX's more compact format brings Vero sound to a wider range of venues. Though smaller in footprint, Vero VX has an equally intelligent acoustic and mechanical design for leading audio quality and ease of use.

The Vero VX system comprises VX90 full-range vertical array elements, V124 or V221 bass enclosures, amp racks, fly bars, transport dollies, ground stack hardware, cabling and Projection system design software.



*Though smaller in footprint, Vero VX
has an equally intelligent acoustic
and mechanical design*









3-WAY VERTICAL ARRAY ELEMENT

The VX90 is a 3-way vertical array element with four new Funktion-One designed Neodymium drivers in a horizontally symmetric configuration:

- Two reflex loaded, high efficiency 12" mid bass drivers
- One Axhead loaded wide bandwidth 8" cone midrange driver
- One 1" compression driver on a proprietary isophase diffraction waveguide



Usable bandwidth is 55Hz to 18kHz. Horizontal dispersion is 90°.



MIDRANGE TECHNOLOGY

Funktion-One's unique driver and waveguide technology enable a single transducer to cover more than four octaves of the audio spectrum, from 300Hz – 5kHz. This approach ensures vocals and musical harmonics are coherent in both time and space, providing benefits in clarity, intelligibility and stereo imaging. The high crossover point to the compression driver provides additional performance advantages, including increased headroom and reduced harmonic and modulation distortion. THD in the midrange is typically <2% (AES2-2012).

EXTRAORDINARY EFFICIENCY


The very high electroacoustic efficiency of the horn-loaded mid/high section is supplemented by new bass driver technology, which significantly increases true power efficiency. The VX's huge LF resource ensures spectral balance and dynamic impact whether used as a single box or in a 24-box array.

Vero VX's extraordinary energy efficiency means up to eight cabinets can be powered from a single amplifier. A 32-box system plus additional subwoofers can be powered by just six amplifiers.

In addition to being a highly flexible standalone system, Vero VX also excels at supporting larger Vero systems with its matched voicing and acoustic design.

SPECIFICATIONS - single cabinet


Usable bandwidth:	55Hz - 18kHz
Sensitivity at 1m	LF: 100dB at 4V MF: 107dB at 4V HF: 109dB at 4V
Horizontal dispersion:	90°
Vertical dispersion:	13°
Nominal impedance:	4 x 16Ω
Rated power:	LF: 2 x 400W MF: 200W HF: 100W
Weight:	70kg (154lbs)
Connectors:	2 x Neutrik NLT8MP



** Calculated peak at 1m with 12dB crest factor pink noise in free field conditions*

LAMBDA RIGGING SYSTEM

The patented Lambda rigging system results from Funktion One's decades of experience with compression rigging methods. This enables cabinets to be transported and flown as straight columns, then a lever hoist is tensioned to compress the cabinets into pre-set angles once the complete array is suspended. The Lambda system's optimised rotation axis ensures perfect alignment at vertical angles between 0-12.5° for coherent summation. There is a choice of fixed or movable point flying beams. The movable point beam incorporates motorised adjustment, enabling the inclination and declination of the entire array to be remotely set while flown from a single motor.



VERO X FEATURES

- Funktion-One wide bandwidth Axhead midrange (300Hz - 5kHz) for natural and effortless vocal clarity
- Isophase diffraction waveguide (HF) for coherent high frequency summation
- Lambda rigging ensures accurate array alignment
- Choice of motorised or static fly beams
- High efficiency drivers giving dynamic headroom, high SPL and low amplifier count
- No corrective EQ, preserving headroom and phase coherency
- Very clean output, even at maximum power
- Gives excellent results when used as a single enclosure



VX90 TRANSPORTATION





The Vero VX speaker system's transport dolly is specifically designed for the various challenges of live events and touring productions. The platform of the dolly is fitted with guides that ensure a Vero VX column settles into the correct position when landing. The guides also work as restraints, securing the load in transit. Each dolly is designed to carry up to five Vero VX enclosures.

Dedicated outriggers can be added for safe ground stacking, enabling overall inclination or declination of the array. Dollies can be stacked for tidy storage during events.





V124

The V124 takes Funktion-One's bass loading and driver technology to the next level. Two 6" voice coils and intense magnetic flux control the 24" cone with impressive accuracy, ensuring excellent transient response and extended depth to below 30Hz.



V221

The V221 is an exceptionally efficient high-intensity bass enclosure with a sensitivity more than 10dB higher than most direct radiating subwoofers. Two 21" drivers provide fast, accurate, bass to 40Hz.



AMPLIFIERS


The Vero VX system is powered by Funktion-One D-Series amplifiers. Both power and processing stages perform to Funktion One's standards of audio fidelity. Four channels of Class D amplification are combined with eight channels of DSP in a single chassis. The four auxiliary DSP outputs can be connected to other Dante receivers, or analogue audio inputs (non-DSP amplifiers or F132As, for example).

D-Series Dante networks are highly robust, with optional dual redundancy, and automatic failsafe to analogue. AudioCore provides remote system control over wired and wireless networks, with a comprehensive preset library for easy system setup and tuning.

Lab Gruppen PLM20K44 presets are available for integration with larger Vero systems.



Up to eight cabinets can be powered from a single amplifier



PROJECTION SOFTWARE

Projection design and prediction software allows Vero VX users to optimise array designs for smooth audience coverage and generate detailed venue specific system information. Projection presents a user friendly interface with many features that make deploying Vero on events and tours straightforward.

Projection has been designed to make the user experience as free flowing as possible



VERO **VX**

Hoyle, Horsham Road, Beare Green, Dorking, Surrey, RH5 4PS, UK Phone : +44 (0)1306 712820 mail@vero-system.com www.vero-system.com

Funktion-One, Vero and Axhead are all registered trademarks