

Evo 6SH

The Evo 6SH is a mid-high, skeletal loudspeaker offering very high output and controlled directivity, whilst weighing just over 20kg.

It can be used in a wide range of applications which include the high power mid-high section of a modular system (for example with F215 mkII and F221/BR221/F124) or in demanding speech based applications such as theatrical voice reinforcement, public address and stadia.

Features:

- Fully horn loaded for high efficiency
- Two-way active (biamp)
- Funktion-One designed drivers
- Low weight Neodymium magnets throughout
- Includes stainless steel mounting yoke
- Optional scrim for discrete appearance
- Evo 6EH version available in wooden enclosure
- Evo 7SH available with narrower dispersion & higher intensity

Frequency Response (-3dB):

250Hz - 18kHz

Weight:

20.5kg (45lbs)

Nominal Dispersion:

50° Horizontal x 25° Vertical

Connectors:

2 x Neutrik NL4



Driver	Crossover Frequencies	Sensitivity (at 1m)*	Power (AES)	Nominal Impedance
10"	220Hz - 4kHz	112dB at 4.9V	250W	24Ω
1.4"	4kHz - Up	114dB at 5.6V	75W	32Ω

*Measured in free field

Specific crossover settings can be found at www.funktion-one.com/support

