

F5.2

F5.2 is the smallest loudspeaker in our Compact Range, making it a valuable tool for the AV installer, bringing Funktion-One sound to distributed audio systems in bars, restaurants and retail applications. F5.2 is equally well suited to domestic listening, home theatre, spatial audio and home DJ monitoring applications.

A Funktion-One specified high sensitivity 5" delivers excellent coherency and builds an impressive image when used in near field situations.

NL4 and Phoenix connector variants are combined into a common connector panel.

Pair with SB8 for discreet, high performance installation or choose SB8A for a very compact self powered Funktion-One system.

2 x F5.2 with 1 x SB8A makes for an outstanding, highly mobile, self-powered small party system.



Features:

- Wide bandwidth 5" driver
- High sensitivity
- Up to 8 units can be connected in parallel
- Angled cabinet for desktop use
- 3/8" microphone stand mount
- Various mounting/rigging options (yoke, wall bracket)
- Optional 70/100V line transformer
- Dual NL4 and Phoenix connector combination as standard
- Weather resistant, IP55 version available

Frequency Response (-3dB):	150Hz - 13kHz
Weight:	2.7kg (5.9lbs)
Nominal Dispersion:	45° Conical
Connectors:	2 x Neutrik NL4 and Phoenix

Driver	Crossover Frequencies	Sensitivity (at 1m)*	Power (AES)	Nominal Impedance
5"	140Hz - Up	90dB at 4V	30W	16Ω

*Measured in free field

Specific crossover settings can be found at www.funktion-one.com/support

