

Evo 7SH

The Evo 7SH is a mid-high skeletal loudspeaker offering very high output and controlled directivity, whilst weighing just over 20kg.

It can be used in a wide range of applications from demanding public address applications to a high power mid-high section in a modular system (for example with F215 mkII and F221/F124).

It has narrower dispersion, with resulting higher intensity, than the Evo 6SH. The two products can be effectively combined to present even coverage and excellent intelligibility for arena and stadia installations.



- Features:
- Horn loaded for high efficiency
 - Two way active (biamp)
 - Funktion-One designed drivers
 - Low weight Neodymium magnets throughout
 - Includes a choice of two stainless steel mounting yokes
 - Evo7EH version available in wooden enclosure

Frequency Response (-3dB): 250Hz - 18kHz
Weight: 23kg (51lbs)
Nominal Dispersion: 40° Horizontal x 20° Vertical
Connectors: 2 x Neutrik NL4

Driver	Crossover Frequencies	Sensitivity (at 1m)*	Power (AES)	Nominal Impedance
10"	220Hz - 4kHz	112dB at 4.9V	250W	24Ω
1.4"	4kHz - Up	114dB at 5.6V	75W	32Ω

*Measured in free field

Specific crossover settings can be found at www.funktion-one.com/support

