

F101.2

F101.2 provides Funktion-One’s renowned sonic performance in a compact and useful form factor. This, along with its outstanding acoustic efficiency, makes F101.2 a highly versatile and cost effective solution for applications including domestic listening, studio monitoring, retail, bars, restaurants and galleries as well as being a handy ‘go to’ for the rental user.

Flared bass reflex ports minimise turbulence and maximise our refined cabinet tuning. A high resolution 1” HF device and Funktion-One designed waveguide delivers precise high frequencies to 20kHz.

F101.2 benefits from our minimalist approach to passive crossover design, achieving very low distortion and excellent integration between drivers, to give a stable and engaging image.

NL4 and Phoenix connector variants are combined into a common connector panel, simplifying purchasing and inventory management.

Combine with SB212 or BR115 for compact full range use.

- Features:
- High sensitivity/electroacoustic energy efficiency
 - Minimalist passive crossover design for maximum resolution
 - Dual NL4 and Phoenix connector combination as standard
 - Various mounting/rigging options (yoke, wall bracket)
 - M8 rigging points
 - Weather resistant IP55 version available

Frequency Response (-3dB): 100Hz - 20kHz
Weight: 10.7kg (23.5lbs)
Nominal Dispersion: 90° Horizontal x 60° Vertical
Connectors: 2 x Neutrik NL4 and Phoenix



Driver	Crossover Frequencies	Sensitivity (at 1m)*	Power (AES)	Nominal Impedance
10" + 1"	100Hz - up	100dB at 2.8V	150W	8Ω

*Measured in free field

Specific crossover settings can be found at www.funktion-one.com/support

