

F88

F88 is a compact yet high output loudspeaker with wide horizontal dispersion, comprising two Funktion-One designed, wide bandwidth 8" drivers with a passive slot tweeter.

Particular attention has been paid to the arrangement of the drive units to optimise coherency. The F88's 110° dispersion and 99dB sensitivity (from 70Hz to 18kHz) allow it to be used in numerous applications including under balcony, theatre, bar, nightclub, cinema surround sound and integrated AV.

The F88 delivers full-range sound and can be given more authority with the addition of Funktion-One bass enclosures - including MB212, F118 or BR118.



- Features:
- Wide dispersion
  - Wide bandwidth
  - Funktion-One designed 8" drivers
  - Choice of grille types

Frequency Response (-3dB): 70Hz - 18kHz  
Weight: 13kg (28.5lbs)  
Nominal Dispersion: 110° Horizontal x 40° Vertical  
Connectors: 2 x Neutrik NL4



Driver	Crossover Frequencies	Sensitivity (at 1m)*	Power (AES)	Nominal Impedance
2 x 8" + HF	60/80Hz - Up	98dB at 2.4V	400W	6Ω

\*Measured in free field

Specific crossover settings can be found at [www.funktion-one.com/support](http://www.funktion-one.com/support)

