

SB10A

Utilising the same design principles as the SB8, the larger SB10 provides higher output and deeper bass. Perfect for applications where a conventionally sized subwoofer is too large and obtrusive, such as bars, restaurants, retail and galleries.

The small size of the SB10 also makes it suitable for domestic applications, such as a dynamic and precise LFE channel in a home theatre system, or as bass extension for the F5.2 or F81.2 in a 2.1 listening or monitoring system.

Integrated 3 channel Class D amplifier with analogue active crossover.

Two Speakon NL4 outputs connect to stereo satellite loudspeakers such as the F81.2.

Features:

- Bespoke high sensitivity 10" bass driver
- Powerful and convincing bass in a very small package
- Integrated 3 channel Class D amplifier
- Balanced XLR inputs (For DJ mixers, pro audio equipment)
- Unbalanced jack inputs (For domestic hifi sources)
- Bass level and polarity controls
- Universal voltage switching power supply with PFC
- Temperature, short circuit and overload protection
- Recommended for use with F81.2

Frequency Response (-3dB):	45Hz - 300Hz
Weight:	19kg (42lbs)
Power output (8Ω):	1x 300W (LF) 2x 75W (Satellites)
Minimum load impedance:	4Ω (Satellites)
Active crossover:	130Hz 24dB Linkwitz-Riley
AC Power:	100-240VAC 50-60Hz 120W
Connectors:	2x XLR 1/4" combo inputs, 2x NL4 outputs, IEC C13

Driver	Crossover Frequencies	Sensitivity (at 1m)*	Power (AES)	Nominal Impedance
10"	40Hz - 130Hz	98dB at 2.8V	300W	8Ω

*Measured in half space

