SB8A

SB8A is an extremely compact, yet powerful and convincing self powered bass loudspeaker. Perfect for applications where a conventionally-sized subwoofer is too large and obtrusive, such as bars, restaurants, retail outlets and galleries. The small size of the SB8A also makes it suitable for consumer applications, such as a dynamic and precise low frequency channel in a home theatre system, or as bass extension for the F5.2, F55 or F81.2 in a 2.1 listening or monitoring system.

Integrated 3 channel Class D amplifier with analogue active crossover. Two Speakon NL4 outputs connect to stereo satellite loudspeakers such as the F5.2.






Features:


- Bespoke high sensitivity 8" bass driver
- · Powerful and convincing bass in a very small package
- Integrated 3 channel Class D amplifier
- Balanced XLR inputs (For DJ mixers, pro audio equipment)
- · Unbalanced jack inputs (For domestic hiff sources)
- · Bass level and polarity controls
- Universal voltage switching power supply with PFC
- Temperature, short circuit and overload protection
- Recommended for use with F5.2

Frequency Response (-3dB): 50Hz - 300Hz Weight: 14kg (38.8lbs) Power output (8 Ω): 1x 300W (LF), 2x 75W (Satellites) Minimum load impedance: 4 Ω (Satellites) Active crossover: 140Hz 24dB Linkwitz-Riley AC Power: 100-240VAC 50-60Hz 120W


Driver	Crossover Frequencies	Sensitivity (at 1m)*	Power (AES)	Nominal Impedance
8"	50Hz - 140Hz	95dB at 2.8V	250W	8Ω

Connectors: 2x XLR 1/4" combo inputs, 2x NL4 outputs, IEC C13









Dimensions in Metric and Imperial

D0065-01

^{*}Measured in half space