

## V60

V60 is the narrow dispersion mid-high element in the Vero system, for far field coverage.

The signature Funktion-One wide bandwidth midrange and three 1.4" compression drivers provide exceptional audio quality to beyond 100m.

It has a nominal directivity of 60° horizontal and 6° vertical with a frequency response of 200Hz to 18kHz. It comprises two 10" Neodymium mid drivers and three 1.4" Neodymium HF drivers in a horizontally symmetric configuration.

### Features:

- Extremely high SPL
- Excellent electroacoustic energy efficiency
- Dynamic audio presentation with excellent stereo imaging
- Meticulously crafted proprietary waveguides and drivers
- Naturally even frequency response
- Integrated flying system for quick and easy deployment



Frequency Response (-3dB): 200Hz - 18kHz  
 Weight: 115kg (254lbs)  
 Nominal Dispersion: 60° Horizontal x 6° Vertical  
 Connectors: 2 x Syntax SPK8 (Male & Female)

Driver	Crossover Frequencies	Sensitivity (at 1m)*	Power (AES)	Nominal Impedance
2 x 10"	220Hz - 4kHz	109dB at 2.8V	500W	12Ω
3 x 1.4"	4kHz - up	112dB at 2.8V	225W	10Ω

\*Measured in free field

Specific crossover settings can be found at [www.funktion-one.com/support](http://www.funktion-one.com/support)

